Working temperature

Storage Temperature

Network System Continous Calls

Charge Input Charging Input

Photo Size

## CCS08 Mini GSM GPS Tracker with Audio Surveillance MMS

|                                    | <ul> <li>Advance survellance device with GSM GPS tracking, MMS and Picture clicking and Audio monitoring</li> <li>Can track live location through web and mobile as well as request the location through sms</li> <li>Video:320*240; Photo Size: 640*480</li> <li>Real time voice surveilance and auto voice call back feature</li> <li>Picture and Video can be requested as MMS by sending a sms command</li> <li>Storage: SD/TF card slot that supports upto 16GB card</li> <li>Built in Li battery of 3.7V 400mAh with battery life of 12 hours on stand by and 5-6 hours in working condition</li> <li>Miniature size for covert operations</li> </ul> |
|------------------------------------|---|
| Specification for mini gps tracker |   |
| Size                               | 35*20*14(L*W*H)   |
| Video                              | 320*240   |
| Product weight:                    | 0.019 kg  |
| GSM/GPS Signal Band                | GSM850/900/1800/1900Mhz   |
| GSM Positioning Time               | 25s   |
| The call current                   | 150mA   |
| Open Sound Control Current         | 30mA  |
| Standby Current                    | 2.5mA   |
| Working Voltage                    | 3.4-4.2 DC  |
| GPRS:                              | Upload60, TCP/IP  |
| Humidity range                     | Non-Condensing 5%-95%   |

×

'-20° to 55° C '-40° to +85 ° C

GSM/GPRS

640\*480

150-180 minutes

110~220V 50/60 Hz

300~500 ma, Output DC 5V